

Version : december 2022

Product code : LP 004

White Coat Extra permanent

Front face Material F 009

A 109 micron matt white film with coating, specially designed for laser printing.

Grammage	approx. 93 g/m ²
Caliper	approx. 100 µ

Adhesive 009

General UV hotmelt adhesive.

Use

General purpose labels and has a excellent adhesion to various substrates including apolar surfaces.

Technical values

Tack : 24 N/ 25mm FTM
Labelling at : 5° C
Service min / max : -20°C/+110°C

Liner K1200

One side coated kraft paper

Weight: 121 gr/m ²
Caliper: 118 µm

Shelf Life

From the date of manufacture: 12 months under Finat defined storage conditions at +20 °C and RH 40%-50%.

Specifications on the use of the material:

The performance of the products should always be tested in the actual application conditions.

A009 complies with European food regulation 1935/2004/EC and with FDA § 175.105. In accordance with the requirements of relevant EU food regulations, the adhesive S3100 may safely stand in direct contact with dry, moist and non-fatty food.

Whitecoat LP004 complies with BS 5609, section 2, Marine Immersion Test.

This publication replaces all previous versions.

Disclaimer

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials. All our products are sold subject to Label Products general sales conditions, and you should ensure that any existing laws are observed. This publication replaces all previous versions. All information is subject to change without notice.